



Internal sounders SP200T, SP203, SP205, SP225



- Range of internal electronic sounders
- Variable output
- Tone selection
- Low current consumption
- High Output
- Encapsulated electronics

■ Technical Specifications

	SP200T	SP203	SP205	SP225
Supply voltage	9...14.5 V DC	9...14 V DC	20...28 V DC	20...28 V DC
Current consumption	140 mA	20...140 mA	08...50 mA	08...50 mA
Output at 1m	110 dB	70...110 dB	70...115 dB	70...115 dB
Tones	1	4	5	5
Dimensions (W x D x H) mm	135 x 35 x 100	135 x 35 x 100	135 x 35 x 100	135 x 35 x 100
IP Rating	IP31	IP31	IP31	IP31
Tamper- Removal & cover	Included	Included	-	-
Construction	ABS White	ABS White	ABS White	ABS Red
Operating temperature	-10...+40°C	-10...+40°C	-10...+50°C	-10...+50°C
Approvals	-	SBSC, DNV, ANPI	-	-

■ Ordering Information

Type	Art.-No.	Description	Weight
SP200T	S54539-Z155-A100	Internal sounder, with tamper	0.23 kg
SP203	S54539-Z147-A100	Internal sounder, with tamper	0.23 kg
SP205	S54539-Z156-A100	Internal sounder	0.23 kg
SP225	S54539-Z157-A100	Internal sounder	0.23 kg

The information in this document includes general descriptions of the technical possibilities, which need not be installed in each individual case. The desired performance characteristics must therefore be specified for the individual case when the contract is concluded.

© Siemens Building Technologies • Edition: 24.09.2014