



## InfoPoint IP812

Access Control

- 
- **Web server booking/reservation functionality**
  - **Includes colour screen**
  - **Built in proximity reader (Cotag or EM)**

InfoPoint is used as a reservation terminal for SiPass Entro and has an integrated function to send and receive information from/to the segment controller (acting as a web server). The InfoPoint uses TCP/IP and works similarly to a web browser in a PC. InfoPoint is supplied with a wall mount kit and a power supply cable (with free end and an RJ45 type of connector). The terminal includes a colour screen and keys for navigating. InfoPoint also has a proximity reader to identify the person who wants to use the unit (either Cotag or EM reading technology).

## Technical data

---

<b>IP812</b>	
Interface	Standard TCP/IP LAN connection, 10BaseT connector. Type RJ45.
Operating voltage	12-24VDC, 12-20VAC. <i>Absolute maximum rating: 10-28VDC / 12-20VAC</i>
Current consumption	540mA @12VDC, 250mA @24VDC.
Screen	Colour TFT screen with the resolution 400 x 240 and 256 colours.
Operating temperature	+5 to +40 °C
Environment	Indoor use only
Housing	Robust stainless steel housing and a strong polycarbonate film is covering the TFT-screen.
Dimensions (W x H x D)	430 x 190 x 58 mm

## Details for ordering

---

Type	Part no	Designation	Weight
IP812-EM	S54513-Z51-A1	InfoPoint with integrated EM reader	2,85 kg
IP812-Cotag	S54513-Z53-A1	InfoPoint with integrated Cotag reader	2,85 kg

Issued by  
Siemens AB  
Security Products  
International Headquarters  
Englundavägen 7  
SE-171 24 Solna  
Tel. +46 8 629 0300

© 2011 Copyright by Siemens AB

Data and design subject to change without notice.  
Supply subject to availability.

[www.siemens.com/securityproducts](http://www.siemens.com/securityproducts)

Document no. **A6V10324508**

Edition 04.2011