



Access Control

SiPass integrated

ATI5100 Intrusion Arming Terminal

-
- Designed to control intrusion areas in a SiPass integrated system
 - Keypad is backlit for convenient and easy use at any time of the day or night
 - LCD screen to display descriptions, messages and prompts to users
 - Status LEDs to inform users of current status information
 - Attractive enclosure designed to suit modern office environments

ATI5100 is a field terminal designed for use with SiPass integrated. It acts as a local interface between an Advanced Central Controller (ACC or ACC-Lite) and authorised cardholders, enabling them to carry out tasks such as arming, part-arming and disarming intrusion alarm areas. If it is connected to a card reader it can also be used as a keypad to enter a PIN.

Technical Data

ATI5100	
Tamper contact	Integrated in housing
Display	LC: 128 x 64 dots 4 lines with 16 characters per line
Operating voltage	9 to 30 VDC
Current consumption	35 to 82 mA @ 12 V
Operating temperature	0 to +50 °C
Relative humidity	93 % (no dew)
Buzzer	Integrated Sound level: Different settings for alarms and key press
Housing	Polycarbonate
IP rating	IP30
Colour	RAL 9003
Weight	0.38 kg
Dimensions (W x H x D)	112 x 185 x 28 mm

Please note that the ATI5100 is not intended for use with Intrunet SI400 series (previously known as Sintony) intrusion systems.

Details for Ordering

Type	Part no.	Designation	Weight
ATI5100	S24246-F2605-A1	Intrusion Arming Terminal	0.38 kg